


LC-X1265P



For standby power supplies.
Expected trickle life: 6 years at 25°C, 10 years at 20°C.


Dimensions (mm)



Specifications

Nominal voltage		12V
Rated capacity (20 hour rate)		65Ah
Dimensions	Length	350 mm
	Width	166 mm
	Height	175 mm
	Total Height	175 mm
Approx. mass		20.0 kg
Country of origin		Republic of China


Discharge characteristics (25°C) (note)



Characteristics

Capacity (note) (25°C)	20 hour rate (3.25A)	65.0Ah
	10 hour rate (5.90A)	59.0Ah
Internal resistance	5 hour rate (10.6A)	53.0Ah
	1 hour rate (40.0A)	40.0Ah
Temperature dependency of capacity (20 hour rate)	1.5 hour rate discharge	26A
	Cut-off voltage 10.5 V	Approx. 7mΩ
Self discharge (25°C)	Fully charged battery (25°C)	Approx. 7mΩ
	40°C	102 %
	25°C	100 %
	0°C	85 %
Charge Method (Constant Voltage)	-15°C	65 %
	Residual capacity after standing 3 months	91%
	Residual capacity after standing 6 months	82%
Trickle use	Residual capacity after standing 12 months	64%
	Control voltage	13.6 to 13.8 V (per 12V cell 25°C)

Duration of discharge vs. Discharge current (note)



(Note) The above characteristics data are average values obtained within three charge/discharge Cycles not the minimum values.